

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) An apparatus comprising:
 - a flexible substrate;
 - a flexible active display supported by the flexible substrate; and
 - a flexible audio transducer proximally disposed with respect to the flexible active display and also supported by the flexible substrate;
 - an acoustic dampener operably coupled between the flexible active display and the flexible audio transducer.
2. (Cancelled)
3. (Currently amended) The apparatus of claim 1 ~~and~~ further comprising at least a second flexible audio transducer proximally disposed with respect to the flexible active display.
4. (Currently amended) The apparatus of claim 3 ~~and further comprising a~~ wherein the flexible substrate that supports the flexible active display; and the flexible audio transducer; ~~and also supports~~ the at least a second flexible audio transducer.
5. (Currently amended) The apparatus of claim 1 ~~and~~ further comprising a plurality of flexible audio transducers disposed substantially equidistant from one another about the flexible active display.

Application No. 10/714,233
Amendment dated November 11, 2004
Reply to Office Action of August 11, 2004

6. (Currently amended) The apparatus of claim 1 ~~and~~ further comprising:

- a first flexible substrate that supports the flexible active display;
- a second flexible substrate that supports the flexible audio transducer.

7. (Cancelled)

8. (Currently amended) The apparatus of claim ~~7~~ 1 wherein the acoustic dampener includes a vacuum disposed therein.

9. (Currently amended) The apparatus of claim ~~7~~ 1 wherein the acoustic dampener comprises a discontinuous material.

10. (Original) The apparatus of claim 9 wherein the discontinuous material comprises a woven structure.

11. (Original) The apparatus of claim 9 wherein the discontinuous material includes a plurality of holes disposed through the material.

12. (Original) The apparatus of claim 6 wherein the first and second flexible substrate are comprised of a similar material.

13. (Original) The apparatus of claim 6 wherein the first and second flexible substrate are comprised of differing materials.

14. (Original) The apparatus of claim 1 wherein the flexible audio transducer is comprised of at least one layer of a dielectric elastomer polymer material.

15. (Original) The apparatus of claim 14 wherein the at least one layer of a dielectric elastomer polymer material has a compliant electrode material disposed on at least one side thereof.

16. (Original) The apparatus of claim 15 wherein the at least one layer of a dielectric elastomer polymer material has a compliant electrode material disposed on both of opposing sides thereof.

17. (Currently amended) The apparatus of claim 1 ~~and~~ further comprising a selective rigidizer disposed proximal to the flexible audio transducer.

18. (Currently amended) The apparatus of claim 1 ~~and~~ further comprising a rigid backing disposed at least partially coextensively with the flexible audio transducer.

19. (Currently amended) The apparatus of claim 1 ~~and~~ further comprising a housing and a retraction mechanism disposed therein that is operably coupled to the flexible active display and the flexible audio transducer.

20. (Currently amended) A method of forming a flexible combined display and speaker apparatus, comprising:

- providing a flexible substrate;
- ~~providing~~ supporting a flexible active display ~~in association~~ with the flexible substrate;
- ~~providing~~ supporting a flexible speaker ~~in association~~ with the flexible substrate;
- disposing an acoustic dampener between the flexible active display and the flexible speaker.

21. (Currently amended) The method of claim 20 ~~and~~ further comprising:

- temporarily disposing the flexible substrate, and hence the flexible active display and the flexible speaker, in a non-planar configuration.

22. (Original) The method of claim 21 wherein temporarily disposing the flexible substrate, and hence the flexible active display and the flexible speaker, in a non-planar configuration comprises rolling the flexible substrate, and hence the flexible active display and the flexible speaker, into a substantially cylindrical shape.

23. (Currently amended) The method of claim 22 ~~and~~ further comprising:

- retractably disposing at least a portion of the substantially cylindrical shape into a housing.

24. (Original) The method of claim 21 wherein temporarily disposing the flexible substrate, and hence the flexible active display and the flexible speaker, in a non-planar configuration comprises folding the flexible substrate.

25. (Currently amended) An integrated display and speaker comprising:

- flexible display means for selectively providing an active display on a conformably flexible display surface;

- flexible speaker means integrally configured with respect to the flexible display means for selectively providing audible sound;

- acoustic dampening means operably and integrally coupled between the flexible display means and the flexible speaker means.

26. (Original) The integrated display and speaker of claim 25 wherein the flexible speaker means comprises a dielectric elastomer polymer.

27. (Original) The integrated display and speaker of claim 26 wherein the dielectric elastomer polymer has a compliant electrode material disposed on at least one side thereof.

28. (Original) The integrated display and speaker of claim 27 wherein the dielectric elastomer polymer has a compliant electrode material disposed on at least two opposing sides thereof.

Application No. 10/714,233
Amendment dated November 11, 2004
Reply to Office Action of August 11, 2004

29. (Original) The integrated display and speaker of claim 28
wherein the compliant electrode material on both sides of the dielectric elastomer polymer
comprises a substantially identical material.

30. (New) The apparatus of claim 1 further comprising a plurality of flexible audio
transducers proximally disposed with respect to the flexible active display and supported by
the flexible active display, wherein at least two of the flexible audio transducers comprise
speakers.